

Product Code 05-2705-81-81

Installation Instructions
3D File
Photometry
Dialux | ULD
Revit (BIM)



Lia LED 600mm

Wall fixture Lia LED 600mm LED 23.1 LED warm-white 3000K ON-OFF Satin nickel 1635lm

Technical features

Luminaire total power: 23.1W

Real lumens: 1635 Real lm/W: 71

Correlated Colour Temperature (CCT): LED warm-white 3000K

Lens / reflector angle: HORIZONTAL 136°

Structure material: Steel Structure finish: Satin nickel Diffuser material: Polycarbonate

Diffuser finish: Opal

Voltage / frequency: 100-240V/50-60Hz

Dimming protocol: ON-OFF

Power Factor: 0.90

Useful life: 50,000h L80B20

Warranty: 5 años











Luminotechnic features

CRI: 80

MacAdam steps: 3

Photobiological risk: RG0 UGR crosswise: 20.7 UGR lengthwise: 15.2

Lampholder	Quantity	Light source power (W)
LED	1	20.8W








Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 05-2705-81-81

Installation Instructions
3D File
Photometry
Dialux | ULD
Revit (BIM)



Lia LED 600mm

Wall fixture Lia LED 600mm LED 23.1 LED warm-white 3000K ON-OFF Satin nickel 1635lm

Logistics

Net weight (kg): 1.37

Packaged weight (kg): 1.99

Packaging: 660mm x 100mm x

130mm

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.