

MINIMA ROUND LED IP65 FIRE-RATED 5770
SKU 1249013

astro



PRODUCT SPECIFICATION

GENERAL

FINISH:	White	CABLE LENGTH:	1000 (mm)
MAIN MATERIAL:	Metal - Mild Steel	GROSS WEIGHT:	0.522 (Kg)
DIMENSIONS:	D: 92mm DIA: 95mm	CLASS:	CE (Class III)
INSTALLATION ORIENTATION:	Ceiling Mount	IP RATING:	IP65
CUT OUT HOLE:	86mm/3-3/8"	BATHROOM ZONE:	Zone 1, 2, 3
RECESS DEPTH:	100 (mm)	VOLTAGE:	Mains 230 (V)
FIRE RATING:	90min	PRODUCT F MARK:	Not suitable for covering with thermal insulation.


LAMP

LIGHT SOURCE:	COB LED	MACADAM ELIPSE:	To Be Advised
MAXIMUM WATTAGE:	6.5W	UGR:	To Be Advised
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	To Be Advised
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	Not Applicable
LUMINOUS FLUX:	525.58 (lm)	ROTATION ADJUSTMENT ANGLE:	Not Applicable
COLOUR TEMP:	2700 (K)	AVERAGE LIFESPAN:	40,000 (Hrs)
CRI:	82	L70:	To Be Advised
R9:	10.4		

ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	50 (Hz)
DIMMABLE:	Yes	DRIVER / BALLAST VOLTAGE:	220-240 (V)
DIMMING METHOD:	Phase - Leading & Trailing Edge	DRIVER AVERAGE LIFESPAN:	40,000 (Hrs)
DRIVER OUTPUT CURRENT:	180 (mA)	EFFICACY:	64.89 (lm/w)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER / BALLAST INCLUDED?	Yes

ADDITIONAL INFORMATION



BOX QUANTITY x 20

PRODUCT ELEVATIONS

