Installation Instructions
Photometry

Rex

PX-0432-BLA

Wall fixture IP54 Rex LED 6.6 LED warm-white 3000K ON-OFF White 680



TECHNICAL FEATURES

IP54 IK08

Luminaire total power : 6.6W

Real lumens : 244

Nominal lumens : 680

Real lm/W : 37

Correlated Colour Temperature (CCT) : LED warm-white 3000K

Lens / reflector angle : FLOOD 81º

Structure material : Aluminium

Structure finish : White

Diffuser material : Glass

Diffuser finish : Transparent

Voltage / frequency : 100-240V/50-60Hz

Dimming protocol : ON-OFF

Power Factor : 0.50

Useful life : 36.000h L70B30

Warranty : 5 Years

Easily recyclable luminaire

LUMINOTECHNIC FEATURES

CRI: 80

MacAdam steps: 3

Photobiological risk: RG1

UGR

UGR crosswise: 20.7

UGR lengthwise: 14.3

Lampholder	Quantity	Light source power (W)
LED	1	5.2W





LOGISTICS

Net weight (kg): 0.42

Packaged weight (kg): 0.47

Packaging: 85mm x 85mm x 85mm

27 Un

LIGHT APPLICATION

Image may not match reference. LEDS C4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature are subject to a tolerance of ±10%.